




# PREMIUM LVT HERRINGBONE RIGID FLOORING

## Technical Data Sheet

# BERGO®

<b>Product details</b>	Article Number	SH25127635	
	EAN Code	N/A	
	Usage Classification	33	
	Manufacturing Standard	EN 10582	Pass
	Dimensions	ISO 24337	635 x 127 mm
	Weight per Package	ISO 24337	11.11 kg
	Area per Package	1.29 m <sup>2</sup>	
	Area per Pallet	90.32 m <sup>2</sup>	
Locking Method	5G		
<b>Technical properties</b>	Wear Resistance	EN 13329 - Annex E	> 3500 cycles
	Impact Resistance	EN 13329	≥ 1800 mm
	Residual Identification	ISO 24343-1	≤ 0,1 mm
	Stain Resistance	EN 423	Groups 1, 2 and 3 : grade 5
	UV Resistance	ISO 105-B02	> 6
	Fire Classification	EN 13501-1	Bfl-S1
	Dimensional Stability	EN ISO 23999	≤ 0,10 %
	Lock Strength	ISO 24334	Long side: > 8 kN/m Short side: N/A (Herringbone)
	Displacement of furniture feet	EN 424	No changes
	Castor Chair	EN 425	In combination with underlay: no visible changes
	Slip Resistance	EN 13893	DS - R10
	Thermal Resistance	EN 12667	0,059 (m <sup>2</sup> K/W)
	Floor Heating	Appropriate for all standard heating systems in cement flooring. NOT appropriate for heating films.	
	Impact Sound Improvement	ISO 717-2	Δ Lw21db (Δ Llin 10db)
<b>Environment</b>	TVOC after 28 days	≤10 ug/m <sup>3</sup>	
	Emissions in the interior air	Decree n.2011-321	A+
	Formaldehyde Group	EN 14041	E1
	REACH (European regulation) Conformity	Compliant	
Plasticizers	DOTP - Virgin PVC - 100% orthophalate free		
<b>Warranty</b>	Warranty Residential	25 years	
	Warranty Commercial	5 years	
<b>Details Description</b>	The advanced Rigid Core technology of Hybrid2 provides high dimensional stability - even when applied to uneven subfloors - as well as exceptional resistance to scuffs, scrapes, dents and other wear and tear.		
<b>Certificates</b>	  		

TDS-BG-HRB-2022.1