

Product details	Article Number	WH25	
	CE/DoP Code	EN 14041	WVH2001
	Usage Classification	EN NF ISO 10874	33 / 42
	Manufacturing Standard	EN ISO 10582	Conform
	Dimensions	EN ISO 24342	308 x 600 mm
	Total Thickness	EN ISO 24346	5 mm
	Core Thickness	EN ISO 24346 2,218	3,45 mm
	Wear Layer Thickness	EN ISO 24340	0,55 mm
	Weight / m ²	EN ISO 23997	8200 g/m ²
	Density		2,1 kg/m ³
	Underlay Type		IXPE
	Planks / box		12
	Area / box		2,218
	Box / pallet		66
m ² / box		146.36	
Technical properties	Abrasion Resistance	EN 13329 - Annex 3	> 2000 cycles
	Abrasion	EN 660-2	T Group
	Residual Indentation	EN ISO 24343-1	≤ 0,15 mm
	Dimensional Stability to Heat	EN ISO 23999	Long. 0.08% / width. 0,02%
	Curling to Heat	EN ISO 23999	≤ 1,0 mm
	Slip Restraint	DIN 51130	R10
		EN 13893	DS : > 0,37
	Chemical Resistance	EN ISO 26987	Class 0
	Colour Fastness to Light	EN ISO 105-B02	≥ 6
	Flammability / Smoke Emissions	EN 13501-1	Bfl-S1
	Castor Chair / Resistance (type W)	ISO 4918:2009	Pass
	Impact Sound Insulation ΔLw	ISO 712-2	18
	Thermal Resistance	EN 12667	0.030 (m ² .K)/W
	Electrostatic Performance	ISO 24334	< 2kV
Lock Strength	ISO 24334	Long side: > 0.85 kN/m Short side: > 0.85 kN/m	
Underfloor Heating Suitability	EN 12524	Suitable for underfloor heating, max 27°C	
Environment	TVOC after 28 days (AgBB test)	ISO 16000-9	≤17 ug/m ³
	VOC emission class (french regulations)	ISO 16000-9	A+
	Formaldehyde Group	EN 717-1	E1
	REACH (European reglementation) Conformity 1907/2006/CE		Conform
	Plasticizer Components	EN 14372	DOTP - Virgin VC - 100% orthophalate free
	Recyclability		100%
Warranty	Warranty Residential		20 years
	Warranty Commercial		10 years

